

Date of issue: 10.10.2025 Revision: 10.10.2025

1 Identification

- · Other means of identification
- · Trade name: OpalescenceTM Boost 35% Non-PF (Mixed)
- · Article number: SDS 390-001.03R01, 1005860, 1005861, 13651, 4487-JP, 4488-JP, 6233-JP
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Professional Dental Bleaching Gel
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Ultradent Products, Inc.

505 W. Ultradent Drive (10200 S)

South Jordan, UT 84095-3942

USA

onlineordersupport@ultradent.com

(800) 552-5512

Ultradent Australia Pty Ltd. Level 22/2 Market Street

Sydney NSW 2000

Australia

Email: info.anz@ultradent.com Toll Free: 1-800-290929

- · Further information obtainable from: Customer Service
- · Emergency telephone number:

CHEMTREC (NORTH AMERICA): +1 (800) 424-9300 (INTERNATIONAL): +(703) 527-3887

2 Hazard(s) Identification

· Classification of the substance or mixture



flame over circle

Oxidising liquids - Category 2 H272 May intensify fire; oxidizer.



corrosion

Eye damage/irritation – Category 1 H318 Causes serious eye damage.



Skin corrosion/irritation – Category 2 H315 Causes skin irritation.

- · Label elements
- · GHS label elements Void
- · Hazard pictograms GHS03, GHS05

(Contd. on page 2)

Date of issue: 10.10.2025 Revision: 10.10.2025

Trade name: OpalescenceTM Boost 35% Non-PF (Mixed)

(Contd. of page 1)

· Signal word Danger

Hazard-determining components of labelling:

Hydrogen Peroxide (>10-≤25 %)

· Hazard statements

H272 May intensify fire; oxidizer.

H315 Causes skin irritation.

H318 Causes serious eye damage.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous	s components:	
56-81-5	Glycerin	>25-≤50%
	♦ Eye damage/irritation – Category 2A, H319	
7722-84-1	Hydrogen Peroxide	>10-≤25%
	Oxidising liquids - Category 1, H271; Skin corrosion/irritation – Category 1A, H314; Nature toxicity - oral – Category 4, H302; Acute toxicity - inhalation – Category 4, H332	
	Synthetic Amorphous, Pyrogenic Silica	<10%
1310-58-3	Potassium Hydroxide	≤2.5%
	Skin corrosion/irritation — Category 1A, H314; Acute toxicity - oral — Category 4, H302	_

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

This product is a viscous gel, therefore chance of inhalation is extremely low.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Date of issue: 10.10.2025 Revision: 10.10.2025

Trade name: OpalescenceTM Boost 35% Non-PF (Mixed)

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

· Suitable extinguishing agents:

Water spray

Use fire extinguishing methods suitable to surrounding conditions.

· Special hazards arising from the substance or mixture

In closed unventilated containers, risk of rupture due to the increased pressure from decomposition. Contact with combustible material may cause fire.

Advice for firefighters:

Use water spray to cool fire exposed surfaces and protect personnel. Move containers from fire area if there isn't any risk.

- · Protective equipment: Wear fully protective suit.
- · Additional information

Move containers from fire area if there isn't any risk.

Cool endangered receptacles with water spray.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Keep people at a distance and stay on the windward side.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Hydrogen Peroxide may be decomposed by adding sodium metabisulfite or sodium sulfite after diluting to about 5%.

Stop the flow of material, if this is without risk.

Combustible materials exposed to hydrogen peroxide should be immediately submerged in or rinsed with large amounts of water to ensure that all hydrogen peroxide is removed. Residual hydrogen peroxide that is allowed to dry (upon evaporation hydrogen peroxide can concentrate) on organic materials such as paper, fabrics, cotton, leather, wood or other combustibles can cause the material to ignite and result in fire.

Dilute with plenty water.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- Precautions for safe handling:

Safety glasses should be used by the patient and doctor. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EN).

(Contd. on page 4)

Date of issue: 10.10.2025 Revision: 10.10.2025

Trade name: OpalescenceTM Boost 35% Non-PF (Mixed)

(Contd. of page 3)

· Information about fire - and explosion protection:

Combustible materials exposed to hydrogen peroxide should be immediately submerged in or rinsed with large amounts of water to ensure that all hydrogen peroxide is removed. Residual hydrogen peroxide that is allowed to dry (upon evaporation hydrogen peroxide can concentrate) on organic materials such as paper, fabrics, cotton, leather, wood or other combustibles can cause the material to ignite and result in fire.

· Storage:

Requirements to be met by storerooms and receptacles:

Provide ventilation for receptacles.

Suitable material for receptacles and pipes: Stainless steel.

Suitable material for receptacles and pipes: Aluminium.

Suitable material for receptacles and pipes: glass.

Store only in the original receptacle.

Information about storage in one common storage facility:

Store away from combustible materials.

Store away from reducing agents.

Store away from metals.

· Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place.

See product labelling.

Keep container tightly sealed.

· Specific end use(s) Professional Dental Bleaching Gel

8 Exposure controls and personal protection

- · Appropriate engineering controls No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

56-81-5 Glycerin

TWA Short-term value: 10 mg/m³ WES Long-term value: 10 mg/m³

tong term value. 10 mg/m

inhalable dust

7722-84-1 Hydrogen Peroxide

WES Long-term value: 1.4 mg/m³, 1 ppm

Synthetic Amorphous, Pyrogenic Silica

TWA Short-term value: 2 mg/m³

1310-58-3 Potassium Hydroxide

WES Peak limitation: 2 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Do not eat or drink while working.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection: Not required.

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet according to WHS Regulations

Date of issue: 10.10.2025 Revision: 10.10.2025

Trade name: OpalescenceTM Boost 35% Non-PF (Mixed)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and Chemical Properties

· General Information

· Appearance:

· Form: Gel

· Colour: Light Orange to Pink

• Odour: Odourless
• Odour threshold: Not determined.

• pH-value at 20 °C: 6.5-8.5

· Change in condition

Melting point/freezing point:
 Initial boiling point and boiling range:
 Flash point:
 Flammability
 Decomposition temperature:
 Undetermined.
 Not applicable.
 Not determined.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower:

Not determined.

Vapour pressure:

Not determined.

Not determined.

Not determined.

1.24 g/cm³

Relative density

Not determined.

Not determined.

Not determined.

Not determined.

Not determined.

Not determined.

· Solubility in / Miscibility with

water: Fully miscible.
Partition coefficient: n-octanol/water: Not determined.

(Contd. on page 6)

Date of issue: 10.10.2025 Revision: 10.10.2025

Trade name: OpalescenceTM Boost 35% Non-PF (Mixed)

(Contd. of page 5)

Viscosity:
Dynamic: Not determined.
Kinematic: Not determined.

· Other information

• Particle characteristics Not applicable.

· Physical state Fluid

10 Stability and Reactivity

· Reactivity No further relevant information available.

- · Thermal decomposition / conditions to be avoided: Decomposes when exposed to heat
- Possibility of hazardous reactions:

Contact with metals, metallic ions, alkalis, reducing agents and organic matter (such as alcohols or terpenes) may produce self-accelerated thermal decomposition.

Reacts with various metals.

Reacts with organic substances.

· Conditions to avoid:

pH Variations

UV rays

Contamination

· Incompatible materials:

Heavy Metals

Combustible Materials

Reducing Agents

Alkalis

Organic materials

· Hazardous decomposition products: Oxygen

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

ATE (Ac	ute Toxicity Estima	tes)	
Oral	LD50	2,041 mg/kg	
Inhalativ	e LC50/4 h	44.9 mg/l	
56-81-5	Glycerin		
Oral	LD50	7,750 mg/kg (guinea pig)	
		4,100 mg/kg (mouse)	
		5,570 mg/kg (rat)	
		27,000 mg/kg (rabbit)	
	LC50 Fish	>5,000 mg/l (Fish)	
Dermal	LD50	>21,900 mg/kg (rat)	
		10,000 mg/kg (rabbit)	
7722-84-	1 Hydrogen Peroxi	de	
Oral	LC50 Fish	16.4 mg/l (Fish)	

on page

Date of issue: 10.10.2025 Revision: 10.10.2025

Trade name: OpalescenceTM Boost 35% Non-PF (Mixed)

		(Contd. of page 6)	
Synthetic Amorphous, Pyrogenic Silica			
Oral	LD50	>5,000 mg/kg (rat) (Oral Test Method)	
	LC50 Fish	>10,000 mg/l (Fish) (Toxicity to fish)	
Dermal	LD50	>2,000 mg/kg (rabbit) (Dermal test method)	
	LC50(Daphnia magna)	>1,000-10,000 mg/l (daphnia) (Toxicity to aquatic invertebrates)	
1310-58-3	1310-58-3 Potassium Hydroxide		
Oral	LD50	214 mg/kg (rat)	
	LC50 Fish	80 mg/l (Fish)	

- · Primary irritant effect:
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eve damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological Information

· Toxicity

· Aquatic toxicity:			
56-81-5 Glycerin			
EC50	>10,000 mg/kg (Bacteria)		

7722-84-1 Hydrogen Peroxide

EC50 1.38 mg/l (Algae)

2.4 mg/l (daphnia)

- Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Do not allow product to reach sewage system.

Dispose of contents/container in accordance with international, federal, state, and local regulations.

(Contd. on page 8)

Date of issue: 10.10.2025 Revision: 10.10.2025

Trade name: OpalescenceTM Boost 35% Non-PF (Mixed)

(Contd. of page 7)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

UN-Number	
ADG, IMDG, IATA	UN2014
UN proper shipping name	
ADG	2014 HYDROGEN PEROXIDE, AQUEOUS SOLUTION
MDG, IATA	HYDROGEN PEROXIDE, AQUEOUS SOLUTION
Transport hazard class(es)	
ADG	
Class	5.1 Oxidising substances.
Label	5.1+8
MDG	
8 1 1 1 1 1 1 1 1 1 1	
Class	5.1 Oxidising substances.
Label	5.1/8
TATA Salah	
Class	5.1 Oxidising substances.
Label	Forbidden
Packing group ADG, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Oxidising substances.
Hazard identification number (Kemler code): EMS Number:	58 F-H,S-Q
Sums Number: Segregation groups	(SGG16) Peroxides
stowage Category	D
Stowage Calegory	SW1 Protected from sources of heat.
Segregation Code	SG16 Stow "separated from" class 4.1
	SG59 Stow "separated from" SGG14-permanganates SG72 See 7.2.6.3.2.

Date of issue: 10.10.2025 Revision: 10.10.2025

Trade name: OpalescenceTM Boost 35% Non-PF (Mixed)

	(Contd. of page
· Transport in bulk according to Annex II of	f Marpol
and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADG	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2014 HYDROGEN PEROXIDE, AQUEOU
<u> </u>	SOLUTION, 5.1 (8), II

15 Regulatory information

· Safety, healt	th and environmental regulations/legislation specific for the substance or mixture	
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
None of the	ingredients is listed.	
· Australian I	nventory of Industrial Chemicals	
7732-18-5	Water	
56-81-5	Glycerin	
7722-84-1	Hydrogen Peroxide	
1310-58-3	Potassium Hydroxide	
9003-01-4	Polyacrylic Acid	
7235-40-7	Trans Beta Carotene	
25322-68-3	Polyethylene Glycol	
· Standard fo	r the Uniform Scheduling of Medicines and Poisons	
7722-84-1	Hydrogen Peroxide	S5, S6, S10
1310-58-3	Potassium Hydroxide	S5, S6, S10
· Australia: P	riority Existing Chemicals	
None of the	ingredients is listed.	

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P8 OXIDISING LIQUIDS AND SOLIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

(Contd. on page 10)

Date of issue: 10.10.2025 Revision: 10.10.2025

Trade name: OpalescenceTM Boost 35% Non-PF (Mixed)

(Contd. of page 9)

· Chemical safety assessment:

Product contains high levels of hydrogen peroxide, which has a known toxicological profile. Product is only to be used by licensed dental professionals using the specified engineering controls.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases from Section 3

H271 May cause fire or explosion; strong oxidizer.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

- · Department issuing SDS: Environmental, Health, and Safety
- · Contact: Customer Service
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

Oxidising liquids - Category 1: Oxidizing liquids - Category 1

Oxidising liquids - Category 2: Oxidizing liquids - Category 2 Acute toxicity - oral - Category 4: Acute toxicity - Category 4

Skin corrosion/irritation - Category 1A: Skin corrosion/irritation - Category 1A

Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2

Eye damage/irritation – Category 1: Serious eye damage/eye irritation – Category 1

Eye damage/irritation - Category 2A: Serious eye damage/eye irritation - Category 2A

ΑU